



ZEBRA

# ZD410-HC Direct Thermal Printer

## HEALTHCARE READY ULTRA-COMPACT 2-INCH PRINTER

Hospitals and clinics need to print high-resolution labels for a wide variety of items, from patient records and patient wristbands to medication prescriptions and tiny specimen vials. To improve productivity and ensure accuracy, the closer printing can be done to the point-of-task, the better. But nurses stations, pharmacies and labs are often pressed for space. Now, the ZD410-HC makes it easy to put high resolution printing right where you need it. Designed for healthcare, this printer is ready for the constant disinfecting and offers a healthcare-compliant power supply. Smaller than a loaf of bread, this ultra-compact printer easily fits on the most space constrained desk or shelf — or you can even mount it on the wall. With its optional 300 dpi printing, the tiniest labels are crisp and legible. This super-fast printer is easy to deploy and easy to use. And Zebra OneCare service maximizes the availability and productivity of your ZD410 printers with unmatched from-the-manufacturer support that covers everything — from worn out printheads to normal wear and tear. The ZD410 — the “fits anywhere” printer that delivers high quality label printing, right where you need it.



### Ultra compact “fits anywhere” printer

The ZD410 is the smallest printer in its class, fitting easily in the most space-constrained desktop or shelf — you can even mount it on a wall.

### Easy to clean and sanitize with a healthcare compliant power supply

Disinfectant-ready plastics and a sealed button interface make the ZD410 easy to clean and disinfect, helping prevent the

spread of germs in hospitals and clinics. And the power supply is IEC 60601-1 compliant for use in healthcare facilities.

### Adaptable to meet your current and future needs

The movable media sensor gives you more media options, including media with off-center black marks, die-cut notches or multiple labels across the width.

With virtually every modern connectivity option, the ZD410 fits into your technology environment now and in the future. Choose from USB, auto-sensing serial or 10/100 Ethernet, as well as the very latest wireless options: 802.11ac Wi-Fi and Bluetooth 4.1. And the ZD410 supports concurrent Wi-Fi and Ethernet connectivity.

If you need new communication or media handling options in the future, no problem. Add serial or Ethernet connectivity, plus a peeler and a cutter, right on site — without taking the ZD410 out of service. The result? Maximum functionality and uptime.

Since the ZD410 is designed to be backwards compatible with existing applications, formats and printer

languages, you can easily upgrade from your aging Zebra LP 2824 Plus — just plug in the ZD410 and you're back up and running. The ZD410 supports Zebra ZPL and EPL printer languages and many non-Zebra languages, making it easy to replace competitive printers.

### Easy to use and troubleshoot

Five status icons — status, pause, data, supplies and network — provide the information needed to keep the ZD410-HC up, running and available. At glance, users can see if the media needs to be replenished, if the network connection is down and more.

### Link-OS for unparalleled ease of management

The ZD410 supports Zebra's Link-OS, a unique software platform that makes it easier than ever to integrate, manage and maintain your printers, from any location. With this innovative highly flexible solution, you can manage one printer, a group of specific printers or all printers anywhere in the world via the cloud. And a quick tap of an NFC-enabled mobile device on the ZD410 provides access to Zebra's extensive knowledge base of information to help quickly resolve everyday printer issues.



THE “FITS ANYWHERE” ZD410 — HIGH-QUALITY LABEL PRINTING WHEREVER YOU NEED IT.

FOR MORE INFORMATION, VISIT [WWW.ZEBRA.COM/ZD410](http://WWW.ZEBRA.COM/ZD410) OR  
OUR GLOBAL CONTACT DIRECTORY AT [WWW.ZEBRA.COM/CONTACT](http://WWW.ZEBRA.COM/CONTACT)

# ZD410-HC Specifications Chart

STANDARD FEATURES	
Direct Thermal print method	
IEC 60601-1 compliant power supply and healthcare wipeable plastics	
ZPL and EPL programming languages	
5 status icon, 3 button user interface	
USB 2.0, USB Host	
Bluetooth low energy	
OpenACCESS™ for easy media loading	
Dual-wall frame construction	
ENERGY STAR qualified	
PHYSICAL CHARACTERISTICS	
<b>Dimensions</b>	8.6 in. L x 4.5 in. W x 6.0 in. H 220 mm L x 115 mm W x 151 mm H
<b>Weight</b>	2.2 lbs./1.0 kg
PRINTER SPECIFICATIONS	
<b>Resolution</b>	203 dpi/8 dots per mm Optional 300 dpi/12 dots per mm
<b>Memory</b>	512 MB Flash; 256 MB SDRAM
<b>Maximum Print Width</b>	2.2 in./56 mm for 203 dpi and 300 dpi
<b>Maximum Print Speed</b>	6 in./152 mm per second (203 dpi) 4 in./102 mm per second (300 dpi)
<b>Media Sensors</b>	Full width, moveable reflective/black mark sensor; multi-position transmissive/gap sensor
<b>Firmware</b>	ZPL II; EPL 2; EPL Line Mode; XML; ZBI
MEDIA CHARACTERISTICS	
<b>Maximum Label Length</b>	39.0 in./991 mm
<b>Maximum Label and Media Width</b>	2.36 in./60 mm
<b>Media Roll Size</b>	5.00 in./127 mm outer diameter Core inner diameter: 0.5 in. (12.7mm) and 1.0 in. (25.4mm) standard, 1.5 in. (38.1), 2.0 in., (50.8mm) and 3.0 in. (76.2mm) using optional adapters
<b>Thickness</b>	0.003 in./0.08 mm - 0.012 in./0.305 mm
<b>Media Types</b>	Roll-fed or fan-fold, die cut or continuous direct thermal labels with or without black mark, tag stock, continuous receipt paper, and wristbands
OPERATING CHARACTERISTICS	
<b>Operating Temp.</b>	40° to 105° F/4.4° to 41° C
<b>Storage Temp.</b>	-40° to 140° F/-40° to 60° C
<b>Operating Humidity</b>	10% to 90% non-condensing
<b>Storage Humidity</b>	5% to 95% non-condensing
<b>Electrical</b>	Auto-detectable (PFC Compliant) 90-265VAC, 50-60Hz; ENERGY STAR qualified

OPTIONS AND ACCESSORIES	
<b>Media Handling</b>	Field installable dispenser – label peel and present with label present sensor; field installable cutter
<b>Communications</b>	Field installable RS-232 auto-sensing Serial, DB-9; Ethernet – 10/100 internal; factory installed wireless dual radio: 802.11ac Wi-Fi and Bluetooth 4.1
<b>Keyboard Display Unit</b>	ZKDU keyboard display units for stand-alone printing solutions
FONTS/GRAPHICS/SYMBOLOGIES	
<b>Barcode Ratios</b>	2:1 and 3:1
<b>1D Barcodes</b>	Code 11, Code 39, Code 93, Code 128, ISBT-128, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2-or 5-digit extensions, Plessey, Postnet, Standard 2-of-5, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Codabar and Planet Code
<b>2D Barcodes</b>	Codablock, PDF417, Code 49, DataMatrix, MaxiCode, QR Code, MicroPDF, Aztec
<b>Fonts and Graphics</b>	16 resident expandable ZPL II bitmap fonts Two resident scalable ZPL fonts Five resident expandable EPL2 fonts Native open-type font support Unicode compliant for multi-language, on demand thermal printing China units include SimSun simplified Chinese font 64 MB user available non-volatile memory, 8 MB user available SDRAM
PRINTER SUPPLIES	
Keep your Zebra printer up and running with genuine Zebra printer supplies, available directly from Zebra.	
REGULATORY	
<ul style="list-style-type: none"> <li>IEC 60950-1, EN55022 Class B, EN55024, EN61000-3-2, EN61000-3-3, FCC Class B, ICES-003, FCC 15.209; 15.247(d), IC RSS 247, EN 300 328, EN 301 893, EN 62311, cTUVus</li> <li>CE Marking, VCCI, C-Tick, S-Mark, CCC, CU, BSMI, KCC, SABS, IN-Metro, BIS, NOM</li> </ul>	
SOFTWARE TOOLS	
<ul style="list-style-type: none"> <li><b>Link-OS: Document Design:</b> Quickly design a customized print solution using your business data and Zebra's intuitive, plug-and-print design tools.</li> <li><b>Device Integration:</b> Zebra offers apps and products designed to help you integrate Zebra devices into your existing systems.</li> <li><b>Device Management:</b> Manage your print operations locally and globally with Zebra's suite of device management tools.</li> <li><b>Developer Tools:</b> Provides you the tools you need to create your own apps, including documentation, source code, programming languages, templates and more.</li> </ul>	
RECOMMENDED SERVICES	
Zebra OneCare Select	

**The ZD410-HC is ideal in space-constrained areas for many healthcare applications, including:**

- Prescription labels
- Patient record labels
- Lab and specimen labeling
- Patient ID wristbands



**NA and Corporate Headquarters**  
+1 800 423 0442  
inquiry4@zebra.com

**Asia-Pacific Headquarters**  
+65 6858 0722  
contact.apac@zebra.com

**EMEA Headquarters**  
zebra.com/locations  
mseurope@zebra.com

**Latin America Headquarters**  
+1 847 955 2283  
la.contactme@zebra.com